


OPTICAL PRE-AMPLIFIER

Description

This high gain semiconductor optical amplifier is primarily intended for use as an optical pre-amplifier in high bit rate applications (10 Gbit/s and 40 Gbit/s). Its high gain and low noise figure provide a high performance, compact and price competitive alternative to single channel EDFAs in receiver subsystems. The optical preamplifier includes a thermistor and thermo-electric cooler in a 14-pin butterfly package with single mode fiber pigtails.



Applications

This product is appropriate for both metro and long haul applications where the use of an optical pre-amplifier increases the sensitivity of the receiver system, particularly where high data rates are used. With appropriate electronic circuitry, the device can be configured to provide a constant output power level over a wide dynamic range of input powers.

Specifications

(C Band 1529-1563nm)


PARAMETER	MIN SPECIFICATION	TYPICAL SPECIFICATION	MAX SPECIFICATION
Fiber-to-fiber gain - (Min)	20dB		
Noise figure		6dB	7dB
Saturation output power	10dBm	11dBm	
Polarisation dependence		0.5dB	1.0dB
Gain ripple		0.3dB	0.5dB
Bias current		200mA	250mA
Operating temp	-5°C		70°C
TEC Drive Max		0.7A/1.5V	

FEATURES

- 1550nm WINDOW
- HIGH GAIN
- LOW POLARISATION DEPENDENCE
- LOW NOISE FIGURE
- COMPACT PACKAGE
- MSA COMPLIANT

Pin Allocation & Package Dimensions

PIN	DEFINITION	PIN	DEFINITION
1	TEC +	8	NC
2	THERMISTOR	9	NC
3	NC	10	SOA ANODE (+)
4	NC	11	SOA CATHODE (-)
5	THERMISTOR	12	NC
6	NC	13	CASE GND
7	NC	14	TEC -



FIBER CONNECTOR	
CODE	CONNECTOR TYPE
FP	FC/PC
FA	FC/APC
FU	FC/UPC
LP	LC/PC
LA	LC/APC
LU	LC/UPC
SP	SC/PC
SA	SC/APC
SU	SC/UPC
∅	None

Ordering Information

OPA - YY - N - W - ZZ

Gain (18 for >18dB and 20 for >20dB are standard)

N = Non isolated is standard

Wavelength (C for C Band is standard)

Connector Type (See Table Above)



Amphotonix reserves the right to make changes in design, specifications and other information at any time, and without prior notice. The information contained within this Data Sheet is believed to be accurate. However, no responsibility is assumed for possible inaccuracy or omission. Any information contained herein shall legally bind Amphotonix only if it is specifically incorporated into the terms and conditions of a sales agreement.

AMPHOTONIX LIMITED

4 Stanley Boulevard, Hamilton International Technology Park, High Blantyre, Glasgow, G72 0BN, United Kingdom
Tel: +44 (0) 1698 722074 Fax: +44 (0) 1698 821101 www.kamelian.com Email: amplifiers@amphotonix.com